







Accessories



Electronic control - sequential starting device for 3 motors code ISO3

Optional see also "accessories" on page 30

Central vacuum cleaner consisting of:

- three silenced SIEMENS turbines with three-phase side channel motor without transmission, star-triangle starting, secured on a metal frame, IP55 safety degree;
- cyclonic dust separator in steel, painted with epoxy powder, secured on a metal frame, filter chamber equipped with industrial-conceived star filter made of special polyester cloth with high withholding properties, deflector for the mechanical-gravitational separation of dust, dirt receptacle on wheels with disposable plastic bags and cushioned fasteners, safety and compensation valves, arranged for pressure compensation system in the dust bag, manual filter shaker predisposed for self-cleaning filter device;
- electric control box with IP55 safety degree, realized in accordance with CEI norms, with low-voltage (12 V) outlet and equipped with electric chart for linkage;
- connections for correct linkage to the piping network and all other parts and accessories for the professional setting of the system

accessories for the professional setting of the system.		
DS F03 125 I		code F125ST
Motor power	Kw	3x5,5
Voltage requirement	V	380-400
Suction power max	mbar 360	inch H ₂ O 144''
Airflow max	m³/h 1640	CFM 965
Airflow @ 140 mbar	m³/h 1210	CFM@56" 712
Filter chamber capacity	l 210	gallons 55
Dirt receptacle capacity	l 125	gallons 28
Filter surface	$cm^2 35.000$	sq. inch 5,425
Motor weight	kg 486	pound 1,071
Motor dimensions hxwxd	cm 185x59,5x97	inch 72.8x23x38,1
Separator weight	kg 95	pound 209
Separator dimensions hxwxd	cm 157x80x72	inch 62x31,5x28
Sound level	dB	78



Automatic filter-shaker device with control box code ISO1



Grill and pipe complete with 2 plastic bags code ISO7



Disposable plastic bag code IE602



Remote control display code IE280



Zinc-coated muffler with couplings code IS11